

CATEGORY 6

Shielded Patch cords

NCB-C6SXXR1-Y



D-Link Cat6 Shielded patch cords are high quality four pair shielded twisted stranded cable terminated with RJ45 modular plugs at both the ends. It is TIA/EIA 568.2-D standard. The shielded cables helps to complete a proper ground connection and allows longer runs with less effect of Electromagnetic Interference (EMI) and Radio Frequency Interference (RFI). These patch cords are appropriate for high speed data transmission.

SPECIFICATIONS

- 4Pairs Individually Shielded Twisted Pair Cable
- Conductor Metal: Bare Copper
- Color Code: Grey
- Conductor: 26 AWG
- Insulation Material: HD-PE
- Overlap Rate: 25%
- Jacket Material: LSZH/PVC
- Heat-resistant: 60oC minimum (Temperature limited)

MODULAR CONNECTOR/PLUG

- RJ-45 8P connector
- Gold plated: 50U"
- Contact blade: Copper Alloy with nickel plated
- Temperature range: -10 ~ 80oC
- Dielectric withstanding voltage: 500V AC
- Insulation resistance: >500MOhm (max.)
- Durability: 750 matching cycles
- Cable-to-plug tensile strength: 20lbs (89N) (min.)

ORDERING INFORMATION

Product No.	Description	Color
NCB-C6SGRYR1-1	Cat6 Shielded 26AWG Patch Cord, 1M	Grey
NCB-C6SGRYR1-2	Cat6 Shielded 26AWG Patch Cord, 2M	Grey
NCB-C6SGRYR1-3	Cat6 Shielded 26AWG Patch Cord, 3M	Grey
NCB-C6SGRYR1-5	Cat6 Shielded 26AWG Patch Cord, 5M	Grey
NCB-C6SGRYR1-1-LS	Cat6 Shielded LSZH 26AWG Patch Cord, 1M	Grey
NCB-C6SGRYR1-2-LS	Cat6 Shielded LSZH 26AWG Patch Cord, 2M	Grey
NCB-C6SGRYR1-3-LS	Cat6 Shielded LSZH 26AWG Patch Cord, 3M	Grey
NCB-C6SGRYR1-5-LS	Cat6 Shielded LSZH 26AWG Patch Cord, 5M	Grey

* Patch cords can be made available in other colors and lengths on bulk orders

* RED-Red, YEL-Yellow, BLU-Blue, GRN-Green, WHI-White

COPPER PATCH CORDS

