

CATEGORY 6A

Shielded Patch cords

NCB-6ASXXR1-Y



D-Link Cat6A shielded patch cords are high quality four pair twisted stranded cable terminated with RJ45 modular plugs at both the ends. It is compliant to the TIA/EIA 568C.2 standard. These patch cords are appropriate for high speed data transmission.

SPECIFICATIONS

- 4Pairs Individually Shielded Twisted Pair Cable
- Conductor Metal: Bare Copper
- Color Code: Grey
- Conductor: 26 AWG
- Insulation Material: HD-PE
- Jacket Material: LSZH/PVC
- Heat-resistant: 75oC minimum (Temperature limited)

MODULAR CONNECTOR/PLUG

- RJ-45 8P connector
- Gold plated: 50U"
- Contact blade: Copper Alloy
- Temperature range: -10 ~ 80oC
- Dielectric withstanding voltage: 500V AC
- Insulation resistance: >500MOhm (max.)
- Durability: 750 matching cycles
- Cable-to-plug tensile strength: 20lbs (89N) (min.)
- Polycarbonate (PC) UL94-V-2

ORDERING INFORMATION

Product No.	Description	Color
NCB-6ASGRYR1-1	Cat6a Shielded 26AWG Patch Cord, 1M	Grey
NCB-6ASGRYR1-2	Cat6a Shielded 26AWG Patch Cord, 2M	Grey
NCB-6ASGRYR1-3	Cat6a Shielded 26AWG Patch Cord, 3M	Grey
NCB-6ASGRYR1-5	Cat6a Shielded 26AWG Patch Cord, 5M	Grey
NCB-6ASGRYR1-1-LS	Cat6a Shielded LSZH 26AWG Patch Cord, 1M	Grey
NCB-6ASGRYR1-2-LS	Cat6a Shielded LSZH 26AWG Patch Cord, 2M	Grey
NCB-6ASGRYR1-3-LS	Cat6a Shielded LSZH 26AWG Patch Cord, 3M	Grey
NCB-6ASGRYR1-5-LS	Cat6a Shielded LSZH 26AWG Patch Cord, 5M	Grey

* Patch cords can be made available in other colors and lengths on bulk orders

* RED-Red, YEL-Yellow, BLU-Blue, GRN-Green, WHI-White

COPPER PATCH CORDS

