DPH-110SE

As a highly user-friendly business IP phone, the D-Link DPH-110SE features a 132×64-pixel graphical LCD that provides a clear visual experience for users. It supports up to two SIP accounts and includes local 5-way conferencing. With its adjustable multi-angle stand, the DPH-110SE ensures flexibility in various working environments.
Additionally, its easy-to-use interface, powerful features, and competitive pricing make it an excellent voice communication solution

Key Features

- Stronger Performance, More Possibilities

Featuring a powerful chipset, the DPH-110 series demonstrates excellent performance, capable of extending services to meet various business demands

- Superior HD Audio, Better Communication

With its leading Smart Noise Filtering Technology, this device delivers excellent sound quality by eliminating extraneous noises, allowing for fluent conversations.

- Classic Design, Practical Details

The DPH-110 features a user-friendly operation interface, offering users a more comfortable and ideal operational experience.

- HD Voice
- 2 SIP accounts
- 132x64 pixel Graphical LCD with Backlight
- Two 10/100M Ethernet Ports
- Support Opus codec
- Support EHS wireless headset
- Local 5-way conferencing
- Stand with 2 adjustable angles
- Wall mountable
- PoE Power

Call Features

- 2 SIP Accounts
- Call Waiting
- Call Forward
- Blind/attended transfer
- Call hold, Call mute, DND mode
- Speed Dialing, Hotline
- Redial, Call Return
- Auto-redial, Auto-answer
- Dial Plan
- 5-way conference
- Peer Dialing

Phone Features

- Adjustable Voice Volume
- Selectable Ring Tones
- XML Browser
- Action URL/URI
- Keyboard lock
- Programmable DSS keys
- Phonebook: 1,000 Groups
- Blacklist: 100 Groups
- Call Log: 100 Logs
- Support 5 Remote Phonebook URLs
- LDAP
- Support Multiple Languages
- Support EHS wireless headset(Plantronics, Jabra, Sennheiser)

Management

- Auto provisioning: FTP/TFTP/HTTP/HTTPS/PnP
- Configuration via HTTP/HTTPS web
- SNMP, TR069
- Network capture
- NTP/Daylight saving time
- Firmware upgrade via web
- Syslog
- Configuration backup/restore

Audio

- HD Voice
- Wideband Codec: G.722, OPUS-WB
- Narrowband Codec: PCMA, PCMU, G.729, G723, G726, AMR, OPUS, iLBC
- Echo Cancellation/Dynamic Jitter
- Voice Activity Detection (VAD)
- Comfort Noise Generation (CNG)
- Full-duplex Speaker

Protocols & Standards

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- SIP over TLS, SRTP
- TCP/IP/UDP
- RTP/RTCP, RFC2198, RFC1889
- HTTP/HTTPS/FTP/TFTP
- ARP/RARP/ICMP/NTP/DHCP
- DNS SRV/ A Query/NATPR Query
- STUN, Session Timer (RFC4028)
- DTMF: In-Band, RFC2833, SIP INFO
- LLDP
- OpenVPN, 802.1X

Physical Features

- 132x64 pixel graphic LCD with backlight
- Dual-angle foot stand: 40° and 45°
- Dimensions(approx.): 180x192x36mm(WxLxD) without foot stand
- Weight(approx.): device 370g, foot stand 60g
- Input voltage: 5Vdc
- Power supply: 5Vdc power adapter or PoE
- Power consumption: 1.4W
- Handset: 4P4C, RJ9
- Headset: 4P4C, RJ9
- Environmental conditions:
  Operation temperature: 0~40°C
  Humidity: 10% to 95%
- 2xRJ45 10/100M Ethernet Ports
- Wall Mountable